(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 18 August 2005 (18.08.2005)

PCT

(10) International Publication Number WO 2005/076359 A1

(51) International Patent Classification⁷: G06K 19/077, H01L 29/786

H01L 27/12,

English

(21) International Application Number:

PCT/JP2005/001739

(22) International Filing Date: 1 February 2005 (01.02.2005)

(26) Publication Language: English

(**30**) **Priority Data:** 2004-030369

(25) Filing Language:

369 6 February 2004 (06.02.2004) J

(71) Applicant (for all designated States except US): SEMI-CONDUCTOR ENERGY LABORATORY CO., LTD. [JP/JP]; 398, Hase, Atsugi-shi, Kanagawa, 2430036 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): ARAI, Yasuyuki [JP/JP]; c/o SEMICONDUCTOR ENERGY LABORATORY CO., LTD., 398, Hase, Atsugi-shi, Kanagawa, 2430036 (JP). TACHIMURA, Yuko [JP/JP]; c/o SEMICONDUCTOR ENERGY LABORATORY CO., LTD.,


398, Hase, Atsugi-shi, Kanagawa, 2430036 (JP). **KANNO, Yohei** [JP/JP]; c/o SEMICONDUCTOR ENERGY LAB-ORATORY CO., LTD., 398, Hase, Atsugi-shi, Kanagawa, 2430036 (JP). **AKIBA, Mai** [JP/JP]; c/o SEMICONDUCTOR ENERGY LABORATORY CO., LTD., 398, Hase, Atsugi-shi, Kanagawa, 2430036 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: SEMICONDUCTOR DEVICE



(57) Abstract: An object of the present invention is providing a semiconductor device that is capable of improving the reliability of a semiconductor element and enhancing the mechanical strength without suppressing the scale of a circuit. The semiconductor device includes an integrated circuit sandwiched between first and second sealing films, an antenna electrically connected to the integrated circuit, the first sealing film sandwiched between a substrate and the integrated circuit, which includes a plurality of first insulating films and at least one second insulating film sandwiched therebetween, the second sealing film including a plurality of third insulating films and at least one fourth insulating film sandwiched therebetween. The second insulating film has lower stress than the first insulting film and the fourth insulating film has lower stress than the third insulating film. The first and third insulating films are inorganic insulating films.

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.